



ICYNENE PROSEAL™

Improved Performance

- Highest available R-value R7* per inch
- One formulation suitable for year round use
- Improved yield for more coverage during application with an average yield of 4,750 board feet
- Higher initial pass of 3" to achieve R21 in one pass
- Drums are not pressurized due to liquid blowing agent, meaning no loss of blowing agent
- One year shelf life
- Standard 'A Side', allowing for better inventory control
- Approved for Type I-V Construction

INDUSTRY TESTING PROSEAL INDUSTRY TEST ASTM E-970 ICC-ES AC377 NFPA 285 ASTM E119 1hr, 2hr, 3hr rating

THERMAL RESISTANCE (R-VALUES) FOR PROSEAL*

THICKNESS (inches)	R-VALUE (°F•ft²•h/Btu)
1	R-7
2	R-14
3	R-21
3.5	R-24
4	R-27
5.5	R-37
6	R-41

IMPROVED FOR OPTIMAL PERFORMANCI

Industry leader Icynene has improved its premier closed cell, medium density product to offer all round improved performance with Icynene ProSeal[™]. Its all-season formulation offers a high R-value of R7 and lets you spray at 23°F to meet today's building code requirements in all climate zones. Plus, the improved formulation provides a greater application yield (average yield of 4,750 board feet) and allows for an initial 3″ pass.

INCREASED ENERGY EFFICIENCY

With a high R-value of R7 per inch, combined with superior air barrier performance, architects and builders can significantly minimize two major sources of heat loss and gain. Typical heating and cooling expenses can be reduced by as much as 50% with Icynene ProSeal™ due to its superior insulating and air-sealing qualities.

CERTIFICATIONS

As a closed cell spray foam, Icynene ProSeal is certified as a Low-Emitting Material (LEM) as per CHPS EQ 2.2 Section 01350 and is recognized as a flood resistant material by the Federal Emergency Management Agency (FEMA).

ICYNENE IS PROUD TO BE ASSOCIATED WITH:







SL-230-01 Updated January 2014 • Product information and specifications subject to change without notice. For the most current product information, please consult Icynene.com. ICYNENE ProSeal™ is a trademark for medium-density, closed-celled foam insulation manufactured by Icynene Inc.

