## **Safety Data Sheet**



## **SECTION 1 – IDENTIFICATION**

Product Name: PITTWRAP® SS jacketing

Manufacturer/Supplier:

Pittsburgh Corning Corporation

800 Presque Isle Drive Information Number: 724-327-6100 Pittsburgh, PA 15239 CHEMTREC: 800/424-9300

Generic Name: Bitumen resin membrane

Use: PITTWRAP® SS jacketing is a self-sealing membrane for protecting underground

FOAMGLAS® insulation systems.

Chemical Family: Mixture

General Comments: General information is available at www.foamglas.com or by using the information

number listed above. General inquiries are typically processed within two business

days.

In event of chemical transportation emergencies involving a spill, leak, fire, exposure, or accident involving the chemical, contact Chemtrec at the number

listed above.

## **SECTION 2 – HAZARD(S) IDENTIFICATION**

HAZARD CLASSIFICATION: Potential Carcinogen

Potential Irritant

SIGNAL WORD: DANGER

HAZARD STATEMENT: May cause cancer.

Repeated or prolonged contact with skin may cause irritation.

Inhalation of heated vapors may cause irritation of nasal passages and

throat.

Eye contact may cause irritation.

HAZARDOUS POLYMERIZATION: Will Not Occur

ROUTES OF EXPOSURE: Inhalation, Skin, Eyes and Ingestion

**IMMEDIATE EFFECTS:** 

INHALATION: Due to the physical nature of this product, inhalation is unlikely. Heated

vapors may cause irritation of nasal passages and throat.

SKIN CONTACT: Normally not irritating. If rash develops or irritation persists, seek.

EYE CONTACT: Due to the physical nature of this product, eye contact is unlikely. Direct

contact can cause irritation. If eye contact is made and irritation develops,

contact a physician.

INGESTION: Due to the physical nature of this product, ingestion is unlikely. If ingested,

contact a physician. Wash hands before eating after using this product.

### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

## PITTWRAP® SS JACKETING

# **Safety Data Sheet**

ACUTE: Inhalation – exposure to heated vapors may cause respiratory, eye, or nose

irritation.

CHRONIC: Inhalation – Long term exposure to concentrated heated vapors may reduce

lung function and cause chronic bronchitis

Carcinogenicity – Components in this product are listed as a carcinogen by NTP, IARC, ACGIH

or OSHA.

**COMPONENT** 

CAS#

Aromatic Oil

64742-04-7

### **SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredient	App. % by wt.	CAS#
Asphalt	45 -55	8052-42-4
Aromatic Oil	5-15	64742-04-7
Carbon Black	10-25	1333-86-4
Petroleum Resins	<2	64742-16-1

### **SECTION 4 - FIRST AID MEASURES**

GENERAL ADVICE: See below.

INHALATION: An unlikely route of entry if used properly. If symptoms develop remove to fresh air.

Consult a physician immediately.

SKIN CONTACT: Normally not irritating. If rash develops or irritation persists, seek physician.

EYE CONTACT: Immediately flush eyes with water for at least 15 minutes while holding eyelids open. Get

immediate medical attention.

INGESTION: An unlikely route of entry. If swallowed, contact a physician immediately. Never give

anything by mouth to an unconscious person. The decision to induce vomiting should only

be made by a physician.

## **SECTION 5 – FIRE FIGHTING MEASURES**

SUITABLE EXTINGUISHING MEDIA: Foam, CO<sub>2</sub>, Dry Chemical. If entering a confined area, use self-

contained breathing apparatus.

**EXPLOSION DATA:** 

SENSITIVITY TO MECHANICAL IMPACT: Stable SENSITIVITY TO STATIC DISCHARGE: Stable

UNUSUAL FIRE AND EXPLOSION HAZARDS: None. This product is not considered flammable.

HAZARDOUS COMBUSTION PRODUCTS: Thermal decomposition may produce smoke, toxic fumes,

Carbon Monoxide, Carbon dioxide, hydrocarbons, and Oxides of

Nitrogen.

SPECIAL FIRE FIGHTING MEASURES: Wear self-contained breathing apparatus and complete personal

protective equipment when potential for exposure to vapors or products of combustion exist. Avoid breathing hazardous vapors or products of combustion, keep upwind. Isolate area and keep

F0AMGLAS® Industry 2 of 6 November 23, 2016

unnecessary people away. Prevent run-off from fire, control or dilution from entering streams or drinking water supplies.

### **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

PRECAUTIONS FOR PERSONNEL: Ensure adequate ventilation. No special clothes are required, but do wear

gloves. Promptly cleanse hands with waterless hand cleaner, clean fingernails and wash with soap and water after handling. Avoid contact with eyes, skin and clothing. Practice good personal hygiene to avoid ingestion. Wash thoroughly after handling and before eating or drinking. Use only with adequate ventilation. Wash clothing before reuse. Refer to

recommendations in section 8.

ENVIRONMENTAL PRECAUTIONS: No special procedures normally needed. Avoid contact with strong

oxidizers like chlorine, pure oxygen or calcium hypochlorite.

PROCESS FOR CLEANING: Scrape up material with non-sparking tools and place in a container fitted

with a lid.

REGULATORY REQUIREMENTS: Follow applicable OSHA regulations (29 CFR 1910.120).

#### **SECTION 7 – HANDLING AND STORAGE**

HANDLING: Avoid direct contact with product. General ventilation is recommended.

STORAGE: Store under dry warehouse conditions away from heat and all ignition sources.

### SECTION 8 – EXPOSURE RESTRICTIONS AND PERSONAL PROTECTION

#### **EXPOSURE LIMITS**

Ingredient	App. % by wt.	TLV	NIOSH REL TWA	PEL	CAS#
Asphalt	45 -55	0.5 mg/m <sup>3*</sup>	0.5 mg/m <sup>3</sup>	NE	8052-42-4
Aromatic Oil	5-15	0.2 mg/m <sup>3*</sup>	0.2 mg/m <sup>3</sup>	0.2 mg/m <sup>3</sup>	64742-04-7
Carbon Black	10-25	3.5 mg/m <sup>3*</sup>	2.4 mg/m <sup>3</sup>	3.5 mg/m <sup>3</sup>	1333-86-4
Petroleum Resins	<2	UŇ	5 mg/m <sup>3</sup>	UŇ	64742-16-1

\*as fumes

EXPOSURE GUIDELINES: See above.

ENGINEERING CONTROLS: Normally not needed, If heating product use local exhaust when

the general ventilation is not sufficient to keep the airborne contaminant concentration below the exposure limit shown above.

PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION: Wear safety glasses or goggles to avoid eye contact.

SKIN PROTECTION: Wear oil impervious gloves to minimize contact with skin. Wear

normal protective work clothing with long sleeved shirt.

RESPIRATORY PROTECTION: Not required under normal conditions of use. Wear appropriate,

properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated above. Follow manufacturer's

directions for respirator use.

ENVIRONMENTAL EXPOSURE CONTROL:

ONTROL: No specific controls are needed.

WORK/HYGIENIC PRACTICES: Avoid contact with eyes and skin. Wash thoroughly after handling

and before eating or drinking.

FOAMGLAS® Industry 3 of 6 November 23, 2016

## **SECTION 9 – PHYSICAL PROPERTIES**

Appearance:	Black bitumen compound with rose colored top film.	Flash Point : °C (°F) TCC	>316(600)
Odor:	asphaltic	Ignition Temperature: °C (°F)	UN
Odor Threshold:	UN	Evaporation Rate (BuAC=1)	NA
pH	NA	Flammability:	Combustible
Molting Point/Eroozing Point: °C (°E	UN	Flammable Limits: LEL	NA
Melting Point/Freezing Point: °C (°F)		UEL	NA
Boiling Point: °C (°F)	UN	Vapor Pressure: (MM Hg): pH:	NA
Solubility in Water:	Insoluble	Vapor Density: (Air = 1)	NA
Partition Coefficient: n-octanol/water:	NE	Specific Gravity: (H <sub>2</sub> 0 = 1):	1.0
Decemposition Temporature	NE	Density: kg/l (lbs./gal)	1.0
Decomposition Temperature	INE	(Calculated)	(8.35)
Viscosity	NA	Evaporation Rate: (BuAC=1)	NA
VOC: g/l (lbs./gal)	0.0 (0.0)	Percent Volatile By Volume: (%)	Negligible

## **SECTION 10 - STABILITY AND REACTIVITY**

REACTIVITY: Can react with strong oxidizers. Material is combustible and

should be stored away from excessive heat and flames.

STABILITY: Stable

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous reaction will not occur

CONDITIONS TO AVOID: Open Flame.

MATERIALS TO AVOID: Strong oxidizers like chlorine, pure oxygen or calcium

hypochlorite

DECOMPOSITION PRODUCTS: Will produce fumes, carbon monoxide, carbon dioxide and

oxides of nitrogen and various other complex hydrocarbons

during combustion.

## **SECTION 11 – TOXICOLOGICAL INFORMATION**

CAS#	INGREDIENT	DERMAL LD50	INHALATION LD50	ORAL LD50
8052-42-4	Asphalt	NE	NE	NE
64742-04-7	Aromatic Oil	NE	NE	NE
1333-86-4	Carbon Black	NE	NE	NE
64742-16-1	Petroleum Resins	> 5000 mg/kg (Rat)	> 4000 mg/kg (Rat)	> 5000 mg/kg (Rat)

CAS#	INGREDIENT	CARCING ACGIH	OGENICITY IARC	TERATOGENICITY	MUTAGENICITY
8052-42-4	Asphalt	NE	NE	NE	NE
64742-04-7	Aromatic Oil	NE	YES	NE	NE
1333-86-4	Carbon Black	NE	NE	NE	NE
64742-16-1	Petroleum Resins	NE	NE	NE	NE

F0AMGLAS® Industry 4 of 6 November 23, 2016

## **SECTION 12 - ECOLOGICAL INFORMATION**

BIODEGRADATION: No information is available. No information is available. AQUATIC TOXICITY: No information is available.

OTHER INFORMATION: None

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

DISPOSAL METHOD: Disposal should be made in accordance with Federal, State and Local regulations.

Before attempting clean up, refer to hazardous information listed on this sheet. Waste of this product is not defined as hazardous according to U.S. EPA (40 CFR § 261.3) Incinerate at EPA (Environmental Protection Agency) approved facility or

dispose of waste in compliance with state and local regulations.

#### **SECTION 14 – TRANSPORT INFORMATION**

SPECIAL SHIPPING INFORMATION: None

DOT SHIPPING CLASS:

TDG

Not regulated.

PIN

Not available

## **SECTION 15 - REGULATORY INFORMATION**

Rotterdam Convention (PIC) Annex III: NA

**US Regulatory Information** 

OSHA 29 CFR 1910-1200 Irritant

TSCA All components of this product are listed on TSCA Inventory

SARA Title III:

SARA SECTION 302: None SARA SECTION 304: None SARA (311,312) HAZARD CLASS: None SARA (313) CHEMICALS: None

CERCLA: NA

RCRA: Refer to section 13

CPSC CLASSIFICATION: NA

HMIS: FLAMMABILITY: 1 REACTIVITY: 0 HEALTH: 1

NFPA: FLAMMABILITY: 1 REACTIVITY: 0 HEALTH: 1

WHMIS CLASSIFICATION: D2B

04115054114	DD 0 D0 01	
CALIFORNIA	PROPOSI	HON 65:

A. This product contains a chemical known to the State of CA to cause birth defects or other i	reproductive harm
------------------------------------------------------------------------------------------------	-------------------

B. This product contains a chemical known to the State of CA to cause cancer.C. This product contains a chemical known to the State of CA to cause cancer and birth defects or other reproductive

harm.

F0AMGLAS® Industry 5 of 6 November 23, 2016

# **Safety Data Sheet**

## **SECTION 16 – OTHER INFORMATION**

Prepared in accordance with 29 CFR 1910.1200

This Product has been classified in accordance with the hazard criteria of the Controlled Products

NEGL = Negligible PROP. = Proprietary

"THE DATA INCLUDED HEREIN ARE PRESENTED IN ACCORDANCE WITH THE VARIOUS ENVIRONMENT, HEALTH AND SAFETY REGULATIONS. IT IS THE RESPONSIBILITY OF A RECIPIENT OF THIS DATA TO REMAIN CURRENTLY INFORMED ON CHEMICAL HAZARD INFORMATION, TO DESIGN AND UPDATE ITS INFORMATION ON CHEMICAL HAZARD INFORMATION, TO DESIGN AND UPDATE ITS OWN PROGRAM AND TO COMPLY WITH ALL NATIONAL, FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS APPLICABLE TO SAFETY, OCCUPATIONAL HEALTH, RIGHT-TO-KNOW AND ENVIRONMENTAL PROTECTION."

WHILE THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE BELIEVED TO BE ACCURATE, PITTSBURGH CORNING MAKES NO WARRANTY WITH RESPECT THERETO, AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

PITTWRAP® and FOAMGLAS® are registered trademarks of Pittsburgh Corning.

F0AMGLAS® Industry 6 of 6 November 23, 2016