

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/11/2020

Supersedes:05/21/2018

Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.
Product code : 46581

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Carburetor Cleaner

1.3. Details of the supplier of the safety data sheet

O'Reilly Auto Parts
233 South Patterson
Springfield, Missouri 65802
T 417-862-2674

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS US classification

Flam. Aerosol 2 H223
Press. Gas (Comp.) H280
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Repr. 2 H361
STOT SE 1 H370
STOT RE 2 H373

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H223 - Flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H361 - Suspected of damaging fertility or the unborn child
H370 - Causes damage to organs
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.
P260 - Do not breathe dust, fumes, gas, mist, vapor spray
P264 - Wash affected areas thoroughly after handling
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P302+P352 - If on skin: Wash with plenty of soap and water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+P311 - If exposed: Call a poison center/doctor.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment: See section 4.1 on SDS
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|---|--------------------|---------|---|
| Acetone | (CAS-No.) 67-64-1 | 70 – 85 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| Carbon Dioxide, Liquefied, Under Pressure | (CAS-No.) 124-38-9 | 10 – 30 | Press. Gas (Comp.), H280 |
| Toluene | (CAS-No.) 108-88-3 | 5 – 10 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 |
| Methanol | (CAS-No.) 67-56-1 | 1 – 5 | Flam. Liq. 2, H225 STOT SE 1, H370 |

The exact percentage is a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation : Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Direct contact with the eyes is likely to be irritating. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/effects after inhalation : Coughing. May cause an allergy or asthma symptoms or breathing difficulties if inhaled. Shortness of breath. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Itching. Red skin. Causes skin irritation.

Symptoms/effects after eye contact : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : Aerosol Level 2.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released product, pump into suitable containers. Plug the leak, cut off the supply.
- Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe dust,fumes,gas,mist,vapor spray.
- Hygiene measures : Wash contaminated clothing before reuse. Wash affected areas thoroughly after handling. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Take off immediately all contaminated clothing and wash it before reuse. Observe normal hygiene standards. Keep container tightly closed. Observe strict hygiene. Reduce/avoid exposure and/or contact.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed. Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
- Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Benzene (71-43-2) | | |
|-------------------|---------------------|--------|
| USA ACGIH | ACGIH TWA (ppm) | 1 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 5 ppm |
| USA ACGIH | ACGIH Ceiling (ppm) | 25 ppm |

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Benzene (71-43-2) | | |
|---|-------------------------------------|------------------------|
| USA OSHA | OSHA PEL (TWA) (ppm) | 1 ppm |
| USA OSHA | OSHA PEL (Ceiling) (ppm) | 5 ppm |
| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 9000 mg/m ³ |
| USA ACGIH | ACGIH TWA (ppm) | 5000 ppm |
| USA ACGIH | ACGIH STEL (mg/m ³) | 54000 |
| USA ACGIH | ACGIH STEL (ppm) | 30000 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 9000 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 5000 ppm |
| Methanol (67-56-1) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 262 mg/m ³ |
| USA ACGIH | ACGIH TWA (ppm) | 200 ppm |
| USA ACGIH | ACGIH STEL (mg/m ³) | 328 mg/m ³ |
| USA ACGIH | ACGIH STEL (ppm) | 250 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 260 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| Acetone (67-64-1) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 1188 mg/m ³ |
| USA ACGIH | ACGIH TWA (ppm) | 500 ppm |
| USA ACGIH | ACGIH STEL (mg/m ³) | 1782 mg/m ³ |
| USA ACGIH | ACGIH STEL (ppm) | 750 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 2400 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| Toluene (108-88-3) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 75 mg/m ³ |
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| USA OSHA | OSHA PEL (Ceiling) (ppm) | 300 ppm |

8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Materials for protective clothing : GIVE EXCELLENT RESISTANCE:
Hand protection : Wear protective gloves.
Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Environmental exposure controls : Avoid release to the environment.
Consumer exposure controls : Avoid contact during pregnancy/while nursing.
Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.
Molecular mass : 58.08 g/mol
Color : Colourless to light yellow.

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---|---|
| Odor | : Acetone odour. Solvent-like odour. |
| Odor threshold | : 306 – 653 ppm 737 – 1574 mg/m ³ |
| pH | : 7 |
| Relative evaporation rate (butyl acetate=1) | : 6 |
| Relative evaporation rate (ether=1) | : 2 |
| Melting point | : -95 °C |
| Freezing point | : -78 °C (Lowest Component-Acetone) |
| Boiling point | : 56 °C (Lowest Component-Acetone) |
| Flash point | : -18 °C (Lowest Component-Acetone) |
| Auto-ignition temperature | : 385 °C (Lowest Component-Acetone) |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : 247 hPa |
| Vapor pressure at 50 °C | : 828 hPa |
| Critical pressure | : 47010 hPa |
| Relative vapor density at 20 °C | : 2 |
| Relative density | : 0.81 |
| Relative density of saturated gas/air mixture | : 1.2 |
| Specific gravity / density | : 809 kg/m ³ |
| Solubility | : Soluble in water. Soluble in ethanol. Soluble in ether. Soluble in dimethyl ether. Soluble in petroleum spirit. Soluble in chloroform. Soluble in dimethylformamide. Soluble in oils/fats. Water: Complete Ethanol: Complete Ether: Complete |
| Partition coefficient n-octanol/water (Log Pow) | : -0.24 (Test data) |
| Partition coefficient n-octanol/water (Log Kow) | : No data available |
| Viscosity, kinematic | : 0.417 mm ² /s |
| Viscosity, dynamic | : 0 Pa·s |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Explosion limits | : 2 – 12.8 vol % 60 – 310 g/m ³ |

9.2. Other information

| | |
|--------------------------|------------------------|
| Minimum ignition energy | : 1.15 mJ |
| Specific conductivity | : 500000 pS/m |
| Saturation concentration | : 589 g/m ³ |
| VOC content | : 9.6 % |
| Gas group | : Compressed gas |

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity : Not classified

| Benzene (71-43-2) | |
|----------------------------|---|
| LD50 oral rat | > 2000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral) |
| LC50 inhalation rat (mg/l) | 43.767 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Female, Experimental value, Inhalation (vapours)) |
| LC50 inhalation rat (ppm) | 13700 ppm (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Female, Experimental value, Inhalation (vapours)) |
| ATE CLP (vapors) | 43.767 mg/l/4h |
| ATE CLP (dust, mist) | 43.767 mg/l/4h |

| Methanol (67-56-1) | |
|----------------------------|---|
| LD50 oral rat | ≥ 2528 mg/kg body weight application as 50% aqueous solution |
| LD50 dermal rabbit | 17100 mg/kg corresponding to 20 ml/kg bw according to the authors |
| LC50 inhalation rat (mg/l) | 128.2 mg/l/4h Air |
| ATE CLP (oral) | 100 mg/kg body weight |
| ATE CLP (dermal) | 300 mg/kg body weight |
| ATE CLP (gases) | 700 ppmV/4h |
| ATE CLP (vapors) | 3 mg/l/4h |
| ATE CLP (dust, mist) | 0.5 mg/l/4h |

| Acetone (67-64-1) | |
|----------------------------|---|
| LD50 oral rat | 5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value) |
| LD50 dermal rabbit | 20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402) |
| LC50 inhalation rat (mg/l) | 71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value) |
| LC50 inhalation rat (ppm) | 30000 ppm/4h (Rat; Experimental value) |

| Toluene (108-88-3) | |
|----------------------------|---|
| LD50 oral rat | 5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value) |
| LD50 dermal rabbit | > 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87) |
| LC50 inhalation rat (mg/l) | > 28.1 mg/l/4h (Rat; Air, Literature study) |
| ATE CLP (oral) | 5580 mg/kg body weight |

Skin corrosion/irritation : Causes skin irritation.
pH: 7

Serious eye damage/irritation : Causes serious eye irritation.
pH: 7

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

| Benzene (71-43-2) | |
|--|---|
| IARC group | 1 |
| National Toxicology Program (NTP) Status | 2 |

| Toluene (108-88-3) | |
|---------------------------|---|
| IARC group | 3 |

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Causes damage to organs.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : Coughing. May cause an allergy or asthma symptoms or breathing difficulties if inhaled. Shortness of breath. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Itching. Red skin. Causes skin irritation.

Symptoms/effects after eye contact : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Benzene (71-43-2) | |
|--------------------------|---|
| LC50 fish 1 | 5.3 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value) |
| EC50 Daphnia 1 | 10 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value) |
| ErC50 (algae) | 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|---|---|
| LC50 fish 1 | 35 mg/l (96 h, Salmo gairdneri, Literature study, Lethal) |

| Methanol (67-56-1) | |
|---------------------------|--|
| LC50 fish 1 | 15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal) |
| EC50 Daphnia 1 | 18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect) |
| ErC50 (algae) | 22000 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value) |

| Acetone (67-64-1) | |
|---|--|
| LC50 fish 1 | 6210 mg/l (96 h; Pimephales promelas; Nominal concentration) |
| EC50 Daphnia 1 | 8800 mg/l (48 h; Daphnia pulex) |
| LC50 fish 2 | 5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss) |
| TLM fish 1 | 13000 ppm (96 h; Gambusia affinis; Turbulent water) |
| TLM fish 2 | > 1000 ppm (96 h; Pisces) |
| Threshold limit other aquatic organisms 1 | 3000 mg/l (Plankton) |
| Threshold limit other aquatic organisms 2 | 28 mg/l (Protozoa) |
| Threshold limit algae 1 | 7500 mg/l (Scenedesmus quadricauda; pH = 7) |
| Threshold limit algae 2 | 3400 mg/l (48 h; Chlorella sp.) |

| Toluene (108-88-3) | |
|---------------------------|---|
| LC50 fish 1 | 5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value) |

12.2. Persistence and degradability

| O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ. | |
|--|------------------|
| Persistence and degradability | Not established. |

| Benzene (71-43-2) | |
|---------------------------------|--|
| Persistence and degradability | Readily biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air. Not established. |
| Biochemical oxygen demand (BOD) | 2.18 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 2.15 g O ₂ /g substance |
| ThOD | 3.1 g O ₂ /g substance |
| BOD (% of ThOD) | 0.7 |

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|---|-----------------------------------|
| Persistence and degradability | Biodegradability: not applicable. |
| Chemical oxygen demand (COD) | Not applicable (inorganic) |
| ThOD | Not applicable (inorganic) |

| Methanol (67-56-1) | |
|---------------------------------|---|
| Persistence and degradability | Readily biodegradable in the soil. Readily biodegradable in water. Not established. |
| Biochemical oxygen demand (BOD) | 0.6 – 1.12 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.42 g O ₂ /g substance |
| ThOD | 1.5 g O ₂ /g substance |

| Acetone (67-64-1) | |
|---------------------------------|---|
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established. |
| Biochemical oxygen demand (BOD) | 1.43 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.92 g O ₂ /g substance |
| ThOD | 2.2 g O ₂ /g substance |
| BOD (% of ThOD) | (20 day(s)) 0.872 |

| Toluene (108-88-3) | |
|---------------------------------|--|
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 2.15 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 2.52 g O ₂ /g substance |
| ThOD | 3.13 g O ₂ /g substance |

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Toluene (108-88-3) | |
|---------------------------|------|
| BOD (% of ThOD) | 0.69 |

12.3. Bioaccumulative potential

| O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ. | |
|--|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | -0.24 (Test data) |
| Bioaccumulative potential | Not established. |

| Benzene (71-43-2) | |
|---|---|
| BCF fish 1 | < 10 (OECD 305: Bioconcentration: Flow-Through Fish Test, 3 day(s), Leuciscus idus, Flow-through system, Fresh water, Experimental value) |
| Partition coefficient n-octanol/water (Log Pow) | 2.13 (Experimental value, 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). Not established. |

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|---|--|
| Partition coefficient n-octanol/water (Log Pow) | 0.83 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |

| Methanol (67-56-1) | |
|---|---|
| BCF fish 1 | 1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value) |
| Partition coefficient n-octanol/water (Log Pow) | -0.77 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). Not established. |

| Acetone (67-64-1) | |
|---|---------------------------------------|
| BCF fish 1 | 0.69 (Pisces) |
| BCF other aquatic organisms 1 | 3 |
| Partition coefficient n-octanol/water (Log Pow) | -0.24 (Test data) |
| Bioaccumulative potential | Not bioaccumulative. Not established. |

| Toluene (108-88-3) | |
|---|---|
| BCF fish 1 | 90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value) |
| Partition coefficient n-octanol/water (Log Pow) | 2.73 (Experimental value, 20 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

12.4. Mobility in soil

| Benzene (71-43-2) | |
|---|---------------------------------------|
| Surface tension | 0.029 N/m (20 °C) |
| Partition coefficient n-octanol/water (Log Koc) | 2.13 (log Koc, Calculated value) |
| Ecology - soil | Low potential for adsorption in soil. |

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|---|-----------------------|
| Ecology - soil | Not applicable (gas). |

| Methanol (67-56-1) | |
|---|--|
| Surface tension | 0.023 N/m (20 °C) |
| Partition coefficient n-octanol/water (Log Koc) | 0.088 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Highly mobile in soil. |

| Acetone (67-64-1) | |
|--------------------------|--------------------|
| Surface tension | 0.0237 N/m (20 °C) |

| Toluene (108-88-3) | |
|---------------------------|---------------------------------------|
| Surface tension | 27.73 N/m (25 °C) |
| Ecology - soil | Low potential for adsorption in soil. |

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity
ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity
IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity
Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols
Flammable, (each not exceeding 1 L capacity)
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT) : LTD QTY - Limited quantity



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 150 kg
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

| O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ. | |
|--|--|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard |
| Benzene (71-43-2) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| CERCLA RQ | 10 lb |
| SARA Section 313 - Emission Reporting | 1 % |
| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| SARA Section 311/312 Hazard Classes | Sudden release of pressure hazard Immediate (acute) health hazard |
| Methanol (67-56-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| CERCLA RQ | 5000 lb |

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Methanol (67-56-1) | |
|--|---|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard |
| SARA Section 313 - Emission Reporting | 1 % |
| Acetone (67-64-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard |
| Toluene (108-88-3) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| CERCLA RQ | 1000 lb |
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard |
| SARA Section 313 - Emission Reporting | 1 % |

15.2. International regulations

CANADA

| O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ. | |
|---|---|
| WHMIS Classification | Class B Division 5 - Flammable Aerosol |
| Benzene (71-43-2) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| Methanol (67-56-1) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
| Acetone (67-64-1) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
| Toluene (108-88-3) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects |

EU-Regulations

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|--|--|
| Methanol (67-56-1) | |
| Acetone (67-64-1) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) | |
| Toluene (108-88-3) | |

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| |
|---|
| Benzene (71-43-2) |
| Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program) Listed on EPA Hazardous Air Pollutant (HAPS) |
| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) |
| Methanol (67-56-1) |
| Listed on EPA Hazardous Air Pollutant (HAPS) |
| Acetone (67-64-1) |
| Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECI (Korean Existing Chemicals Inventory) Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List) |
| Toluene (108-88-3) |
| Listed on EPA Hazardous Air Pollutant (HAPS) |

15.3. US State regulations

| | |
|---|------------------------------------|
| O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ. | |
| U.S. - California - Proposition 65 - Carcinogens List | Yes |
| U.S. - California - Proposition 65 - Developmental Toxicity | Yes |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Yes |
| State or local regulations | U.S. - California - Proposition 65 |

| | | | | |
|---|---|---|---|----------------------------------|
| Benzene (71-43-2) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| Yes | Yes | No | Yes | |

| | | | | |
|---|---|---|---|----------------------------------|
| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | No | No | No | |

| | | | | |
|---|---|---|---|----------------------------------|
| Methanol (67-56-1) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | Yes | No | No | |

| | | | | |
|---|---|---|---|----------------------------------|
| Acetone (67-64-1) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| Yes | Yes | No | Yes | |

| | | | | |
|---|---|---|---|----------------------------------|
| Toluene (108-88-3) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| Yes | Yes | No | Yes | |

| | | | | |
|--|--|--|--|--|
| Benzene (71-43-2) | | | | |
| State or local regulations | | | | |
| U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities | | | | |

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzene (71-43-2)

U.S. - Idaho - Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York City - Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - West Virginia - Air Quality - Toxic Air Pollutant Emission Limits

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

State or local regulations

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York City - Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

Methanol (67-56-1)

State or local regulations

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York City - Right to Know Hazardous Substances List

Acetone (67-64-1)

State or local regulations

U.S. - California - Proposition 65
Benzene 71-43-2
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Toluene (108-88-3)

State or local regulations

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York City - Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revision - See : *

Other information : None.


Full text of H-phrases:

| | |
|------|---|
| H223 | Flammable aerosol |
| H225 | Highly flammable liquid and vapour |
| H280 | Contains gas under pressure; may explode if heated |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H336 | May cause drowsiness or dizziness |
| H361 | Suspected of damaging fertility or the unborn child |
| H370 | Causes damage to organs |
| H373 | May cause damage to organs through prolonged or repeated exposure |

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

O'REILLY CARB COMPLIANT CARBURETOR CLEANER 12.5 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability : 3 Serious Hazard
Physical : 1 Slight Hazard
Personal protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied. Published by: Kaylon Gonzales