

DOC ID: SWD-SDS-**PMG-040** REV. 00 EFF. DATE: 08/15/19 APPROVAL: MGMT. REP. <u>ON FILE</u>

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: QS A

Product Name: Quik-Shield A
Company Name: SWD URETHANE

539 S. Drew St. Mesa, AZ 85210,

Web site address: www.swdurethane.com

Emergency Contact: CHEMTREC (800) 424-9300

2. HAZARDS IDENTIFICATION

Acute Toxicity: Oral, Category 5 Skin Corrosion/Irritation, Category 2 Skin Sensitization, Category 1

Serious Eye Damage/Eye Irritation, Category 2B

Acute Toxicity: Inhalation, Category 4
Respiratory Sensitization, Category 1

Carcinogenicity, Category 2





GHS Signal Word: Danger

GHS Hazard Phrases: H303 - May be harmful if swallowed.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H320 - Causes eye irritation. H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351 - Suspected of causing cancer.

H401 - Toxic to aquatic life.

GHS Precaution Phrases: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P284 - Wear respiratory protection.

P285 - In case of inadequate ventilation wear respiratory protection.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P341 - If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+313 - IF exposed or concerned: Get medical attention/advice. P332+313 - If skin irritation occurs, get medical advice/attention. P337+313 - If eye irritation persists, get medical advice/attention.

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 2 of 8

DOC ID: SWD-SDS-PMG-040 REV. 00 EFF. DATE: 08/15/19

P342+311 - If experiencing respiratory symptoms call a POISON CENTER or

doctor/physician.

P362 - Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal

Phrases:

P405 - Store locked up.

Inhalation: Causes respiratory tract irritation.

May be harmful if absorbed through the skin. Causes skin irritation. Skin Contact:

Eve Contact: Causes eye irritation.

May be harmful if swallowed. Ingestion:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS# Ingredients/Components Concentration

9016-87-9 Polymeric diphenylmethane diisocyanate

(Isocyanic acid, Poly

0.0 -100.0 %

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

If breathed in, move person into fresh air. If not breathing give artificial respiration. In Case of Inhalation:

In Case of Skin Contact: Wash off with soap and plenty of water. Consult a physician.

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. In Case of Eye Contact:

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water.

Consult a physician.

Signs and Symptoms Of

Exposure:

Cough, Shortness of breath, Headache. Nausea. Vomiting, Pulmonary edema. Effects

may be delayed.

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of Note to Physician:

dangerous area.

5. FIRE FIGHTING MEASURES

> 150.00 C Method Used: Closed Cup Flash Pt: LEL: UEL: **Explosive Limits:**

Autoignition Pt: NA

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

Wear self contained breathing apparatus for fire fighting if necessary. Fire Fighting Instructions:

Flammable Properties and

Hazards:

Hazardous Combustion

Products:

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case

Material Is Released Or

Spilled:

Personal precautions.

Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Ensure

adequate ventilation.

Environmental precautions. Do not let product enter drains.

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers

for disposal.

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.

Page: 3 of 8

DOC ID: SWD-SDS-PMG-040 REV. 00 EFF. DATE: 08/15/19

7. HANDLING AND STORAGE

Precautions To Be Taken in

Avoid contact with skin and eyes. Avoid formation of dust and aerosols.

Provide appropriate exhaust ventilation at places where dust is formed. Normal

measures for preventive fire protection.

Precautions To Be Taken in

Keep container tightly closed in a dry and well-ventilated place.

Storing:

Handling:

Recommended storage temperature: 15 - 38 deg.C.

Store under inert gas. Moisture sensitive.

EXPOSURE CONTROLS/PERSONAL PROTECTION 8.

CAS# **Partial Chemical Name OSHA TWA ACGIH TWA** Other Limits

9016-87-9 Polymeric diphenylmethane

diisocyanate (Isocyanic acid, Poly

Respiratory Equipment

(Specify Type):

When the product is sprayed or heated without adequate ventilation, an approved MSHA/NIOSH positive-pressure, supplied air respirator may be required. Air purifying

respirators equipped with organic vapor cartridges and HEPA (P100) particulate filter may be used under certain conditions when the cartridge change-out schedule has been

developed in accordance with the OSHA respiratory protection standard (29 CFR

1910.134).

Eye Protection: Face shield and safety glasses.

Protective Gloves: Handle with gloves.

Other Protective Clothing: Choose body protection according to the amount and concentration of the dangerous

substance at the work place.

Engineering Controls

(Ventilation etc.):

Work/Hygienic/Maintenance Handle in accordance with good industrial hygiene and safety practice. Wash hands

Practices: before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] Gas [X] Liquid **Physical States:** [] Solid

Slightly. Musty. Appearance and Odor:

pH:

Melting Point: 42.00 C - 45.00 C

Boiling Point: 200.00 C

> 150.00 C Method Used: Closed Cup Flash Pt:

Evaporation Rate:

Flammability (solid, gas):

LEL: UEL: **Explosive Limits:**

1

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): Specific Gravity (Water = 1):

1.18 G/CM3 Density:

Solubility in Water:



Page: 4 of 8

DOC ID: SWD-SDS-PMG-040 REV. 00 EFF. DATE: 08/15/19

Octanol/Water Partition

Coefficient:

Autoignition Pt: NA **Decomposition Temperature:**

Viscosity:

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid -Contact with moisture, other materials that react with isocyanates, or temperatures above

350 °F (177 °C), may cause polymerization. Instability:

Incompatibility - Materials To Water. Amines, Strong bases, Alcohols.

Avoid:

Hazardous Decomposition or formed under fire conditions. Carbon oxides,

nitrogen oxides (NOx). **Byproducts:**

Possibility of Hazardous

Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid -Hazardous Reactions:

11. TOXICOLOGICAL INFORMATION

CAS# 9016-87-9: Toxicological Information:

Not reported., LC50, Not reported., Rat, 490.0 MG/M3.

Results:

Behavioral: Somnolence (general depressed activity). Behavioral: Convulsions or effect on seizure threshold.

- National Technical Information Service, Vol/p/yr: OTS05, 6728

Not reported., LD50, Dermal, Rat, 490.0 MG/L.

Results:

Behavioral: Somnolence (general depressed activity). Behavioral: Convulsions or effect on seizure threshold.

Not reported., LC50, Not reported., Rat, 490.0 MG/M3.

Results:

Kidney, Ureter, Bladder: Renal function tests depressed.

Blood:Other changes.

Irritation or Corrosion: Serious eye damage/eye irritation:

Eyes - rabbit - Moderate eye irritation.

Carcinogenicity/Other

Carcinogenicity.

Information: This product is or contains a component that is not classifiable as to its carcinogenicity

based on its IARC, ACGIH, NTP, or EPA classification.

Limited evidence of carcinogenicity in animal studies.

IARC: Group 3: Not classifiable as to its carcinogenicity to humans 3.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by OSHA.



Page: 5 of 8

DOC ID: SWD-SDS-**PMG-040** REV. 00 EFF. DATE: 08/15/19

CAS # Ingredients/Components NTP IARC ACGIH OSHA

9016-87-9 Polymeric diphenylmethane diisocyanate (Isocyanic acid,

Poly

12. ECOLOGICAL INFORMATION

Persistence and

No data available.

Degradability:

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Product.

Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an

3

afterburner and scrubber.

Contaminated packaging.

Dispose of as unused product.

14. TRANSPORT INFORMATION

Additional Transport Information:

Not regulated except when shipped in bulk. Bulk containers (>9 000 lbs) must be transported as: ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S.

(Methylene Diphenyl Diisocyanate), Class 9, UN3082, PG III, RQ.

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Other regulated substances, Liquid, N.O.S. (Methylene Diphenyl Diisocyanate)

DOT Hazard Class: 9 CLASS 9

UN/NA Number: NA3082 Packing Group: III



LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Not Regulated.

UN Number: 3082 Packing Group: III

Hazard Class: 9 - CLASS 9 TDG Classification:

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Not Regulated.

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Not Regulated.





DOC ID: SWD-SDS-**PMG-040** REV. 00 EFF. DATE: 08/15/19

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS # Ingredients/Components S. 302 (EHS) S. 304 RQ S. 313 (TRI)
9016-87-9 Polymeric diphenylmethane diisocyanate No No Yes-Cat. N120

{Isocyanic acid, Poly

CAS # Ingredients/Components Other US EPA or State Lists

9016-87-9 Polymeric diphenylmethane diisocyanate CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -

{Isocyanic acid, Poly

Inventory, 8C, 8D TERM; CA PROP.65: No; CA TAC, Title 8:

No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No;

NJ EHS: Yes - Cat.; NY Part 597: No; PA HSL: No; SC TAP:

No; WI Air: No

CAS # Ingredients/Components International Regulatory Lists

9016-87-9 Polymeric diphenylmethane diisocyanate Canadian DSL: Yes; Canadian NDSL: No

{Isocyanic acid, Poly

Regulatory Information: This product contains chemicals subject to the reporting requirements of section 313 of

Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40

CFR part 372.

Incipient fire responders should wear eye protection. Firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other

environmentally sensitve areas.

Incipient fire responders should wear eye protection. Firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can

be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other

environmentally sensitve areas.

16. OTHER INFORMATION

Revision Date: 12/12/2018

Additional Information About

This Product:

Company Policy or

Disclaimer:

While the information and recommendations in this publication are given to the best of our knowledge, and information at the date of publication, nothing herein is to be construed as a warranty, expressed or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information, and recommendations or the suitability of any product for its own particular purpose.

The product may present hazards and should be used with caution. While certain hazards are described in this Safety Data Sheet, no guarantee is made that these are the only hazards that exist. Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED SWD EMPLOYEE SHALL PROVIDE, OR MAKE AVAILABLE, DATA SHEETS FOR SWD PRODUCTS.

DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 7 of 8

DOC ID: SWD-SDS-**PMG-040** REV. 00 EFF. DATE: 08/15/19

THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT THE WRITTEN PERMISSION OF SWD. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET OR QUESTIONS REGARDING THIS DATA SHEET SHOULD BE DIRECTRED TO SWD AT 800-828-1394.



Page: 1 of 8

DOC ID: SWD-SDS-**PMG-108** REV. 00 EFF. DATE: 08/15/19 APPROVAL: MGMT. REP. <u>ON FILE</u>

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: QS 108 B

Product Name: Quik-Shield 108 B
Company Name: SWD URETHANE

539 S. Drew St. Mesa, AZ 85210,

Web site address: www.swdurethane.com

Emergency Contact: CHEMTREC (800) 424-9300

2. HAZARDS IDENTIFICATION

Acute Toxicity: Oral, Category 4
Acute Toxicity: Skin, Category 5
Skin Corrosion/Irritation, Category 3

Serious Eye Damage/Eye Irritation, Category 2B

Skin Corrosion/Irritation, Category 2

Serious Eye Damage/Eye Irritation, Category 1

Flammable Liquids, Category 4
Acute Toxicity: Skin, Category 3
Acute Toxicity: Inhalation, Category 2
Skin Corrosion/Irritation, Category 1A
Skin Corrosion/Irritation, Category 1B
Skin Corrosion/Irritation, Category 1C
Acute Toxicity: Oral, Category 5





GHS Signal Word: Danger

GHS Hazard Phrases: H227 - Emergency Considerations: Emergency responders must wear the proper

personal protective equipment suitable for the situation to which they are responding.

H302 - Harmful if swallowed.

H303 - May be harmful if swallowed. H311 - Toxic in contact with skin.

H313 - May be harmful in contact with skin.

H314 - Causes severe skin burns and eye damage.

H315 - Causes skin irritation.H316 - Causes mild skin irritation.H318 - Causes serious eye damage.

H320 - Causes eye irritation. H330 - Fatal if inhaled.

H402 - Harmful to aquatic life.

GHS Precaution Phrases: P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P284 - Wear respiratory protection .

GHS Response Phrases: P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 2 of 8

DOC ID: SWD-SDS-**PMG-108** REV. 00 EFF. DATE: 08/15/19

unwell.

P302+352 - IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/physician.

P321 - Specific treatment see ... on this label.

P330 - Rinse mouth.

P332+313 - If skin irritation occurs, get medical advice/attention. P337+313 - If eye irritation persists, get medical advice/attention. P361 - Remove/Take off immediately all contaminated clothing.

P363 - Wash contaminated clothing before reuse.

GHS Storage and Disposal

P403+235 - Store in cool/well-ventilated place.

Phrases:

P405 - Store locked up.

P501 - Preparing Wastes for Disposal: Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU

Member States and Japan.

RCRA Waste Code: None Listed

EU Waste Code: None Listed.

Inhalation: May be harmful if inhaled. Causes respiratory tract irritation. Material is irritating to

mucous membranes and upper respiratory tract.

Skin Contact: May be harmful if absorbed through the skin. Causes skin irritation. Causes burns. Skin

Absorption: Toxic if absorbed through skin.

Eye Contact: Causes eye irritation. Causes burns. Causes eye burns.

Ingestion: Harmful if swallowed. Harmful if swallowed.

Small intestine. Large intestine.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#		Hazardous Components (Chemical Name)	Concentration	
	NA	Halogenated Phosphate	30.0 -50.0 %	
	9082-00-2	Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-Propanetriol (3:1)	10.0 -25.0 %	
	9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	0.0 -10.0 %	
	NA	Non Emissive Amine Catalyst	5.0 -10.0 %	



Page: 3 of 8

DOC ID: SWD-SDS-**PMG-108** REV. 00 EFF. DATE: 08/15/19

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

In Case of Inhalation: If breathed in, move person into fresh air. If not breathing give artificial respiration. If

inhaled, remove to fresh air. Consult a physician.

In Case of Skin Contact: Wash off with soap and plenty of water. Consult a physician. In case of contact,

immediately wash skin with soap and copious amounts of water. In case of skin contact, flush with copious amounts of water for at least 15 minutes. Call a physician. Take off

contaminated clothing and shoes immediately.

In Case of Eye Contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. In

case of contact, immediately flush eyes with copious amounts of water for at least 15 minutes. In case of contact with eyes, flush with copious amounts of water for at least 15

minutes. Assure adequate flushing by separating the eyelids with fingers. Call a

physician. Continue rinsing eyes during transport to hospital.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water.

Consult a physician. If swallowed, wash out mouth with water provided person is conscious. Call a physician. Call a physician immediately. Do NOT induce vomiting.

Signs and Symptoms Of

Exposure:

To the best of our knowledge, the chemical, physical, and toxicological properties have

not been thoroughly investigated. Skin rash. Damage to the liver. Asthma.

Gastrointestinal disturbances. Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin. Inhalation may result in spasm, inflammation and edema of the larynxand bronchi, chemical pneumonitis, and pulmonary edema. Symptoms of exposure may include burning sensation, coughing, wheezing,

laryngitis, shortness of breath, headache, nausea, and vomiting. Cough,

Shortness of breath, Headache,

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of

dangerous area.

5. FIRE FIGHTING MEASURES

Flash Pt:

Explosive Limits: LEL: UEL:

Autoignition Pt:

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. Suitable: For

small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide.

For large fires, apply water from as far as possible.

Fire Fighting Instructions: Wear self contained breathing apparatus for fire fighting if necessary. Protective

Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Emits toxic fumes under fire conditions.

Flammable Properties and

Hazards:

Hazardous Combustion

Products:

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Spilled:

SAFETY DATA SHEET Quik-Shield 108 B

Page: 4 of 8

DOC ID: SWD-SDS-**PMG-108** REV. 00 EFF. DATE: 08/15/19

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or

Personal precautions.

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure

adequate ventilation.

Environmental precautions.

Do not let product enter drains.

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in

suitable, closed containers for disposal. PROCEDURE(S) OF PERSONAL

PRECAUTION(S)

Wear respirator, chemical safety goggles, rubber boots, and heavy rubber gloves.

Methods for cleaning up.

Absorb on sand or vermiculite and place in closed containers for disposal. Ventilate area and wash spill site after material pickup is complete. PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL. Evacuate area. Wear self-contained breathing apparatus,

rubber boots, and heavy rubber gloves.

7. HANDLING AND STORAGE

Precautions To Be Taken in

Handling:

Avoid inhalation of vapor or mist.

Normal measures for preventive fire protection. User Exposure: Avoid contact with eyes,

skin, and clothing.

Precautions To Be Taken in

Storing:

Keep container tightly closed in a dry and well-ventilated place. Suitable: Keep tightly

closed. Keep away from heat and open flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
NA	Halogenated Phosphate			
9082-00-2	Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-Propanetriol (3:1)			
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)			
NA	Non Emissive Amine Catalyst			

Respiratory Equipment

(Specify Type):

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN

(EU). Hand: Compatible chemical-resistant gloves.

Eye Protection: Face shield and safety glasses. Chemical safety goggles. Tightly fitting safety goggles.

Faceshield (8-inch minimum). Use equipment for eye protection tested and approved

under appropriate government standards such as NIOSH (US) or EN 166(EU).

Protective Gloves: Handle with gloves. Eyes: Chemical safety goggles. Use proper glove removal technique

(without touching glove's outer surface) to avoid skin contact with this product. Wash and

dry hands.

Other Protective Clothing: Choose body protection according to the amount and concentration of the dangerous

substance at the work place. Complete suit protecting against chemicals.

Engineering Controls

(Ventilation etc.):

Mechanical exhaust required. Safety shower and eye bath. Use only in a chemical fume

hood.

Work/Hygienic/Maintenance

Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash

contaminated clothing before reuse. Discard contaminated shoes. EXPOSURE LIMITS,

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 5 of 8

DOC ID: SWD-SDS-**PMG-108** REV. 00 EFF. DATE: 08/15/19

RTECS.

Country Source Type Value. USA ACGIH TWA 0.05 PPM

Remarks: Skin. STEL 0.15 PPM EXPOSURE LIMITS. USA TWA 0.05 ppm USA STEL 0.15 ppm

9.	PHYSICAL AND CHEMICAL PR	ROPERTIES
Physical States:	[] Gas [X] Liquid [] Solid	
Appearance and Odor:	amber. Musty.	
pH:		
Melting Point:		
Boiling Point:		
Flash Pt:		
Evaporation Rate:		
Flammability (solid, gas): Explosive Limits:	LEL: UEL:	
Vapor Pressure (vs. Air or	<u> </u>	
mm Hg):		
Vapor Density (vs. Air = 1):		
Specific Gravity (Water = 1):		
Solubility in Water:		
Octanol/Water Partition Coefficient:		
Autoignition Pt:		
Decomposition Temperature:		
Viscosity:		
	10. STABILITY AND REACT	IVITY
Stability:	Unstable [] Stable [X]	
Conditions To Avoid - Instability:	No data available.	
Incompatibility - Materials To Avoid:	To Strong oxidizing agents. Mineral acids, acids (organic, sodium hypochlorite). Corrodes metal. Avoid moisture. Avoid direct Sunlight. Avoid excessive temperatures.	
· ·	ous Decomposition or formed under fire conditions. Carbon oxides,	
Byproducts:	Phosphorous oxides, Hydrogen chloride gas,	
	Thermal decomposition 244 °C Carbon mono Ammonia, Nitric acid, nitrogen oxides (NOx).	
Possibility of Hazardous	Will occur [] Will not occur [X]	
Reactions:		
Conditions To Avoid -		

Hazardous Reactions:



Page: 6 of 8

DOC ID: SWD-SDS-**PMG-108** REV. 00 EFF. DATE: 08/15/19

11. TOXICOLOGICAL INFORMATION

Toxicological Information: CAS# NA:

Acute toxicity, LD50, Oral, Rat, 3600. MG/KG.

Results:

Behavioral: Somnolence (general depressed activity).

Behavioral: Tremor.

Lungs, Thorax, or Respiration:Other changes.

- National Technical Information Service, Vol/p/yr: OTS05, 7713

Acute toxicity, LD50, Intravenous, Mouse, 56.00 MG/KG.

Results:

Behavioral: Food intake (animal).

Nutritional and Gross Metabolic:Weight loss or decreased weight gain.

- U.S. Army Armament Research & Development Command, Chemical Systems Laboratory, NIOSH Exchange Chemicals., Aberdeen Proving Ground,, Aberdeen

Proving Ground, MD 21010, Vol/p/yr: NX#, 5768

Skin corrosion/irritation, Skin sensitization, This product does not contain any relevant quantities of materials with critical values that have to be monitored in the workplace.,

Rabbit, 0.000, Mild.

Results:

Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Eye: Lacrimation.

Behavioral: Tremor.

Lungs, Thorax, or Respiration:Cyanosis.

Irritation or Corrosion: Skin - rabbit - Mild skin irritation - 24 h.

Serious eye damage/eye irritation:

Skin - rabbit - Corrosive.

Eyes - rabbit - Severe eye irritation.

Carcinogenicity/Other

Information:

Carcinogenicity.

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by OSHA.

CAS # Hazardous Components (Chemical Name) NTP IARC ACGIH OSHA

NA Halogenated Phosphate

9082-00-2 Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-Propanetriol (3:1)

9046-10-0 *Poly(oxy(methyl-1,2-ethanediyl)

NA Non Emissive Amine Catalyst



Page: 7 of 8

DOC ID: SWD-SDS-**PMG-108** REV. 00 EFF. DATE: 08/15/19

12. ECOLOGICAL INFORMATION

Persistence and No data available.
Degradability: Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Product.

Observe all federal, state, and local environmental regulations. Contact a licensed

professional waste disposal service to dispose of this material.

Contaminated packaging.

Dispose of as unused product. APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION. This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and

non-recyclable solutions to a licensed disposal company.

14. TRANSPORT INFORMATION

GHS Classification: Acute Toxicity: Oral, Category 4 - Warning! Harmful if swallowed

Acute Toxicity: Skin, Category 5 - Warning! May be harmful in contact with skin Skin Corrosion/Irritation, Category 3 - Warning! Causes mild skin irritation

Serious Eye Damage/Eye Irritation, Category 2B - Warning! Causes eye irritation

Aquatic Toxicity (Acute), Category 3 - Harmful to aquatic life

Skin Corrosion/Irritation, Category 2 - Warning! Causes skin irritation

Serious Eye Damage/Eye Irritation, Category 1 - Danger! Causes serious eye damage

Flammable Liquids, Category 4 - Warning! Combustible liquid Acute Toxicity: Skin, Category 3 - Danger! Toxic in contact with skin

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name:

DOT Hazard Class: UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name:

UN Number:

Hazard Class: TDG Classification:

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Non-Hazardous for Air Transport: Non-hazardous for air transport. UN Number:

2927 Hazard Class: 6.1 Packing Group: II.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
NA	Halogenated Phosphate	No	No	No
9082-00-2	Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-Propanetriol (3:1)	No	No	No
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	No	No	No
NA	Non Emissive Amine Catalyst	No	No	No



Page: 8 of 8

DOC ID: SWD-SDS-**PMG-108** REV. 00 EFF. DATE: 08/15/19

CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists
NA	Halogenated Phosphate	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8D TERM; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
9082-00-2	Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-Propanetriol (3:1)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
NA	Non Emissive Amine Catalyst	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
CAS#	Hazardous Components (Chemical Name)	International Regulatory Lists
NA	Halogenated Phosphate	Canadian DSL: Yes; Canadian NDSL: No
9082-00-2	Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-Propanetriol (3:1)	Canadian DSL: Yes; Canadian NDSL: No
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	Canadian DSL: Yes; Canadian NDSL: No
NA	Non Emissive Amine Catalyst	Canadian DSL: No; Canadian NDSL: No

16. OTHER INFORMATION

Revision Date: 04/03/2015

Additional Information About

This Product: