

1 / 6

For the most current version of this MSDS visit www.Versico.com.**Material Safety Data Sheet****G200SA YELLOW SUBSTRATE ADHESIVE****MSDS No. 302141**

Date of Preparation: 9/15/14

Revision: 024

Section 1 - Chemical Product and Company Identification**Product/Chemical Name:** G200SA YELLOW SUBSTRATE ADHESIVE**Chemical Formula:** Mixture**General Use:** Contact Bonding Adhesive**Manufacturer:** Versico, 1285 Ritner Highway, Carlisle, PA 17013, Phone: 800-992-7663**Emergency Phone Number:** CHEMTREC (USA) 800-424-9300**Section 2 - Hazards Identification****☆☆☆☆ Emergency Overview ☆☆☆☆**

Danger – Highly flammable liquid and vapor

Warning – Causes skin irritation

Warning – Causes eye irritation

Warning – May be harmful if swallowed and enters airway

Danger – May damage fertility or the unborn child

Warning – May cause an allergic skin reaction

Warning – Suspected of causing genetic defects (skin)

Warning – May cause drowsiness and dizziness

Warning – May cause damage to organs (liver, kidney, ear) through prolonged or repeated exposure

HMIS

H 1

F 4

R 0

PPE†

†Sec. 8

Potential Health Effects**Primary Entry Routes:** Skin contact, skin absorption, eye contact, inhalation, ingestion.**Target Organs:****Acute Effects****Inhalation:** throat irritation on short-term exposure to liquid or vapor. Aspiration into lungs can cause chemical pneumonitis, which can be fatal.**Eye:** irritation on short-term exposure to liquid or vapor.**Skin:** irritation on short-term exposure to liquid or vapor.**Ingestion:** ingestion can cause gastrointestinal irritation**Carcinogenicity:** IARC, NTP, and OSHA do not list this product as a carcinogen.**Medical Conditions Aggravated by Long-Term Exposure:** Respiratory symptoms associated with pre-existing lung disorders and pre-existing heart disorders may be aggravated by exposure to this material.**Chronic Effects:** Overexposure may result in headache, dizziness, fatigue, nausea, and possible unconsciousness, even asphyxiation. Moderate irritation of skin, eyes and mucous membranes of upper respiratory tract on prolonged/repeated contact. Dermatitis and defatting of the skin. Chronic exposure may cause reversible liver and kidney injury.

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Repeated exposure to Toluene has been associated with high frequency hearing loss based on animal tests.

Section 3 – Ingredient Information

Hazardous Ingredients	CAS Number	% wt
Acetone	67-64-1	5-10
Solvent Naptha(SN), Light Aliphatic(LA),(Heptane)	64742-89-8	15-40
Toluene	108-88-3	30-60
Xylene	1330-20-7	1-5
Magnesium Oxide	1309-48-4	0.5-1.5
Additional Ingredients	CAS Number	% wt
Polychloroprene	Proprietary	
Phenolic Resin	Proprietary	

2 / 6

For the most current version of this MSDS visit www.Versico.com.**Material Safety Data Sheet****G200SA YELLOW SUBSTRATE ADHESIVE****MSDS No. 302141**

Date of Preparation: 9/15/14

Revision: 024

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: G200SA YELLOW SUBSTRATE ADHESIVE
Chemical Formula: Mixture
General Use: Contact Bonding Adhesive
Manufacturer: Versico, 1285 Ritner Highway, Carlisle, PA 17013, Phone: 800-992-7663
Emergency Phone Number: CHEMTREC (USA) 800-424-9300

Section 2 - Hazards Identification**☆☆☆☆ Emergency Overview ☆☆☆☆**

Danger – Highly flammable liquid and vapor
 Warning – Causes skin irritation
 Warning – Causes eye irritation
 Warning – May be harmful if swallowed and enters airway
 Danger – May damage fertility or the unborn child
 Warning – May cause an allergic skin reaction
 Warning – Suspected of causing genetic defects (skin)
 Warning – May cause drowsiness and dizziness
 Warning – May cause damage to organs (liver, kidney, ear) through prolonged or repeated exposure

HMIS

H 1
 F 4
 R 0

PPE†

†Sec 8

Potential Health Effects**Primary Entry Routes:** Skin contact, skin absorption, eye contact, inhalation, ingestion.**Target Organs:****Acute Effects****Inhalation:** throat irritation on short-term exposure to liquid or vapor. Aspiration into lungs can cause chemical pneumonitis, which can be fatal.**Eye:** irritation on short-term exposure to liquid or vapor.**Skin:** irritation on short-term exposure to liquid or vapor.**Ingestion:** ingestion can cause gastrointestinal irritation**Carcinogenicity:** IARC, NTP, and OSHA do not list this product as a carcinogen.**Medical Conditions Aggravated by Long-Term Exposure:** Respiratory symptoms associated with pre-existing lung disorders and pre-existing heart disorders may be aggravated by exposure to this material.**Chronic Effects:** Overexposure may result in headache, dizziness, fatigue, nausea, and possible unconsciousness, even asphyxiation. Moderate irritation of skin, eyes and mucous membranes of upper respiratory tract on prolonged/repeated contact. Dermatitis and defatting of the skin. Chronic exposure may cause reversible liver and kidney injury.

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Repeated exposure to Toluene has been associated with high frequency hearing loss based on animal tests.

Section 3 – Ingredient Information

Hazardous Ingredients	CAS Number	% wt
Acetone	67-64-1	5-10
Solvent Naptha(SN), Light Aliphatic(LA),(Heptane)	64742-89-8	15-40
Toluene	108-88-3	30-60
Xylene	1330-20-7	1-5
Magnesium Oxide	1309-48-4	0.5-1.5
Additional Ingredients	CAS Number	% wt
Polychloroprene	Proprietary	
Phenolic Resin	Proprietary	

3 / 6

For the most current version of this MSDS visit www.Versico.com.**Material Safety Data Sheet****G200SA YELLOW SUBSTRATE ADHESIVE****MSDS No. 302141**

Date of Preparation: 9/15/14

Revision: 024

Section 1 - Chemical Product and Company Identification**Product/Chemical Name:** G200SA YELLOW SUBSTRATE ADHESIVE**Chemical Formula:** Mixture**General Use:** Contact Bonding Adhesive**Manufacturer:** Versico, 1285 Ritner Highway, Carlisle, PA 17013, Phone: 800-992-7663**Emergency Phone Number:** CHEMTREC (USA) 800-424-9300**Section 2 - Hazards Identification****☆☆☆☆ Emergency Overview ☆☆☆☆**

Danger – Highly flammable liquid and vapor

Warning – Causes skin irritation

Warning – Causes eye irritation

Warning – May be harmful if swallowed and enters airway

Danger – May damage fertility or the unborn child

Warning – May cause an allergic skin reaction

Warning – Suspected of causing genetic defects (skin)

Warning – May cause drowsiness and dizziness

Warning – May cause damage to organs (liver, kidney, ear) through prolonged or repeated exposure

HMIS

H 1

F 4

R 0

PPE†

†Sec. 8

Potential Health Effects**Primary Entry Routes:** Skin contact, skin absorption, eye contact, inhalation, ingestion.**Target Organs:****Acute Effects****Inhalation:** throat irritation on short-term exposure to liquid or vapor. Aspiration into lungs can cause chemical pneumonitis, which can be fatal.**Eye:** irritation on short-term exposure to liquid or vapor.**Skin:** irritation on short-term exposure to liquid or vapor.**Ingestion:** ingestion can cause gastrointestinal irritation**Carcinogenicity:** IARC, NTP, and OSHA do not list this product as a carcinogen.**Medical Conditions Aggravated by Long-Term Exposure:** Respiratory symptoms associated with pre-existing lung disorders and pre-existing heart disorders may be aggravated by exposure to this material.**Chronic Effects:** Overexposure may result in headache, dizziness, fatigue, nausea, and possible unconsciousness, even asphyxiation. Moderate irritation of skin, eyes and mucous membranes of upper respiratory tract on prolonged/repeated contact. Dermatitis and defatting of the skin. Chronic exposure may cause reversible liver and kidney injury.

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Repeated exposure to Toluene has been associated with high frequency hearing loss based on animal tests.

Section 3 – Ingredient Information

Hazardous Ingredients	CAS Number	% wt
Acetone	67-64-1	5-10
Solvent Naptha(SN), Light Aliphatic(LA),(Heptane)	64742-89-8	15-40
Toluene	108-88-3	30-60
Xylene	1330-20-7	1-5
Magnesium Oxide	1309-48-4	0.5-1.5
Additional Ingredients	CAS Number	% wt
Polychloroprene	Proprietary	
Phenolic Resin	Proprietary	

4 / 6

For the most current version of this MSDS visit www.Versico.com.**Material Safety Data Sheet****G200SA YELLOW SUBSTRATE ADHESIVE****MSDS No. 302141**

Date of Preparation: 9/15/14

Revision: 024

Section 1 - Chemical Product and Company Identification**Product/Chemical Name:** G200SA YELLOW SUBSTRATE ADHESIVE**Chemical Formula:** Mixture**General Use:** Contact Bonding Adhesive**Manufacturer:** Versico, 1285 Ritner Highway, Carlisle, PA 17013, Phone: 800-992-7663**Emergency Phone Number:** CHEMTREC (USA) 800-424-9300**Section 2 - Hazards Identification****☆☆☆☆ Emergency Overview ☆☆☆☆**

Danger – Highly flammable liquid and vapor

Warning – Causes skin irritation

Warning – Causes eye irritation

Warning – May be harmful if swallowed and enters airway

Danger – May damage fertility or the unborn child

Warning – May cause an allergic skin reaction

Warning – Suspected of causing genetic defects (skin)

Warning – May cause drowsiness and dizziness

Warning – May cause damage to organs (liver, kidney, ear) through prolonged or repeated exposure

HMIS

H 1

F 4

R 0

PPE†

†Sec. 8

Potential Health Effects**Primary Entry Routes:** Skin contact, skin absorption, eye contact, inhalation, ingestion.**Target Organs:****Acute Effects****Inhalation:** throat irritation on short-term exposure to liquid or vapor. Aspiration into lungs can cause chemical pneumonitis, which can be fatal.**Eye:** irritation on short-term exposure to liquid or vapor.**Skin:** irritation on short-term exposure to liquid or vapor.**Ingestion:** ingestion can cause gastrointestinal irritation**Carcinogenicity:** IARC, NTP, and OSHA do not list this product as a carcinogen.**Medical Conditions Aggravated by Long-Term Exposure:** Respiratory symptoms associated with pre-existing lung disorders and pre-existing heart disorders may be aggravated by exposure to this material**Chronic Effects:** Overexposure may result in headache, dizziness, fatigue, nausea, and possible unconsciousness, even asphyxiation. Moderate irritation of skin, eyes and mucous membranes of upper respiratory tract on prolonged/repeated contact. Dermatitis and defatting of the skin. Chronic exposure may cause reversible liver and kidney injury.

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Repeated exposure to Toluene has been associated with high frequency hearing loss based on animal tests.

Section 3 – Ingredient Information

Hazardous Ingredients	CAS Number	% wt
Acetone	67-64-1	5-10
Solvent Naptha(SN), Light Aliphatic(LA),(Heptane)	64742-89-8	15-40
Toluene	108-88-3	30-60
Xylene	1330-20-7	1-5
Magnesium Oxide	1309-48-4	0.5-1.5
Additional Ingredients	CAS Number	% wt
Polychloroprene	Proprietary	
Phenolic Resin	Proprietary	

For the most current version of this MSDS visit www.Versico.com.

Material Safety Data Sheet

G200SA YELLOW SUBSTRATE ADHESIVE

MSDS No. 302141

Date of Preparation: 9/15/14

Revision: 024

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: G200SA YELLOW SUBSTRATE ADHESIVE
Chemical Formula: Mixture
General Use: Contact Bonding Adhesive
Manufacturer: Versico, 1285 Ritner Highway, Carlisle, PA 17013, Phone: 800-992-7663
Emergency Phone Number: CHEMTREC (USA) 800-424-9300

Section 2 - Hazards Identification

☆☆☆☆ Emergency Overview ☆☆☆☆

Danger – Highly flammable liquid and vapor Warning – Causes skin irritation Warning – Causes eye irritation Warning – May be harmful if swallowed and enters airway Danger – May damage fertility or the unborn child Warning – May cause an allergic skin reaction Warning – Suspected of causing genetic defects (skin) Warning – May cause drowsiness and dizziness Warning – May cause damage to organs (liver, kidney, ear) through prolonged or repeated exposure	<table border="0"> <tr><td>HMIS</td></tr> <tr><td>H 1</td></tr> <tr><td>F 4</td></tr> <tr><td>R 0</td></tr> <tr><td>PPE†</td></tr> <tr><td>†Sec. 8</td></tr> </table>	HMIS	H 1	F 4	R 0	PPE†	†Sec. 8
HMIS							
H 1							
F 4							
R 0							
PPE†							
†Sec. 8							

Potential Health Effects

Primary Entry Routes: Skin contact, skin absorption, eye contact, inhalation, ingestion.
Target Organs:
Acute Effects
Inhalation: throat irritation on short-term exposure to liquid or vapor. Aspiration into lungs can cause chemical pneumonitis, which can be fatal.
Eye: irritation on short-term exposure to liquid or vapor.
Skin: irritation on short-term exposure to liquid or vapor.
Ingestion: ingestion can cause gastrointestinal irritation
Carcinogenicity: IARC, NTP, and OSHA do not list this product as a carcinogen.
Medical Conditions Aggravated by Long-Term Exposure: Respiratory symptoms associated with pre-existing lung disorders and pre-existing heart disorders may be aggravated by exposure to this material.
Chronic Effects: Overexposure may result in headache, dizziness, fatigue, nausea, and possible unconsciousness, even asphyxiation. Moderate irritation of skin, eyes and mucous membranes of upper respiratory tract on prolonged/repeated contact. Dermatitis and defatting of the skin. Chronic exposure may cause reversible liver and kidney injury. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Repeated exposure to Toluene has been associated with high frequency hearing loss based on animal tests.

Section 3 – Ingredient Information

Hazardous Ingredients	CAS Number	% wt
Acetone	67-64-1	5-10
Solvent Naptha(SN), Light Aliphatic(LA),(Heptane)	64742-89-8	15-40
Toluene	108-88-3	30-60
Xylene	1330-20-7	1-5
Magnesium Oxide	1309-48-4	0.5-1.5
Additional Ingredients	CAS Number	% wt
Polychloroprene	Proprietary	
Phenolic Resin	Proprietary	

6 / 6

For the most current version of this MSDS visit www.Versico.com.**Material Safety Data Sheet****G200SA YELLOW SUBSTRATE ADHESIVE****MSDS No. 302141**

Date of Preparation: 9/15/14

Revision: 024

Section 1 - Chemical Product and Company Identification**Product/Chemical Name:** G200SA YELLOW SUBSTRATE ADHESIVE**Chemical Formula:** Mixture**General Use:** Contact Bonding Adhesive**Manufacturer:** Versico, 1285 Ritner Highway, Carlisle, PA 17013, Phone: 800-992-7663**Emergency Phone Number:** CHEMTREC (USA) 800-424-9300**Section 2 - Hazards Identification****☆☆☆☆ Emergency Overview ☆☆☆☆**

Danger – Highly flammable liquid and vapor

Warning – Causes skin irritation

Warning – Causes eye irritation

Warning – May be harmful if swallowed and enters airway

Danger – May damage fertility or the unborn child

Warning – May cause an allergic skin reaction

Warning – Suspected of causing genetic defects (skin)

Warning – May cause drowsiness and dizziness

Warning – May cause damage to organs (liver, kidney, ear) through prolonged or repeated exposure

HMIS

H 1

F 4

R 0

PPE†

†Sec 8

Potential Health Effects**Primary Entry Routes:** Skin contact, skin absorption, eye contact, inhalation, ingestion.**Target Organs:****Acute Effects****Inhalation:** throat irritation on short-term exposure to liquid or vapor. Aspiration into lungs can cause chemical pneumonitis, which can be fatal.**Eye:** irritation on short-term exposure to liquid or vapor.**Skin:** irritation on short-term exposure to liquid or vapor.**Ingestion:** ingestion can cause gastrointestinal irritation**Carcinogenicity:** IARC, NTP, and OSHA do not list this product as a carcinogen.**Medical Conditions Aggravated by Long-Term Exposure:** Respiratory symptoms associated with pre-existing lung disorders and pre-existing heart disorders may be aggravated by exposure to this material.**Chronic Effects:** Overexposure may result in headache, dizziness, fatigue, nausea, and possible unconsciousness, even asphyxiation. Moderate irritation of skin, eyes and mucous membranes of upper respiratory tract on prolonged/repeated contact. Dermatitis and defatting of the skin. Chronic exposure may cause reversible liver and kidney injury.

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Repeated exposure to Toluene has been associated with high frequency hearing loss based on animal tests.

Section 3 – Ingredient Information

Hazardous Ingredients	CAS Number	% wt
Acetone	67-64-1	5-10
Solvent Naptha(SN), Light Aliphatic(LA),(Heptane)	64742-89-8	15-40
Toluene	108-88-3	30-60
Xylene	1330-20-7	1-5
Magnesium Oxide	1309-48-4	0.5-1.5
Additional Ingredients	CAS Number	% wt
Polychloroprene	Proprietary	
Phenolic Resin	Proprietary	